

PRODUCT SUBMITTAL

Ceiling Hanger Wire (For Suspended Grid Systems)




Commercial-Grade Acoustical Ceiling Products

- For suspended ceiling grid systems
- Several gauges available (standard 12 ga.)
- Variety of lengths available (standard 12 ft.)
- Mill galvanized, 1008 Brite Basic or stainless steel available
- Nominal Tensile: 55,000 – 70,000 psi
- **Specification Data Available Upon Request**



shipped fully enclosed, custom wood crate with lid

MATERIAL CONFORMANCE DETAILS	PRODUCT STANDARDS												
<p>Straightened and Cut Wire is manufactured for use in the installation of suspended ceiling grid systems to provide an efficient method of attachment from structural roof members to grid cross members.</p> <p>Several gauges of factory-galvanized wire are available in standard lengths of 12 ft to ensure proper installation according to applicable design criteria.</p> <p>Special lengths of wire are available upon request.</p> <p>Special gauges of wire are available upon request.</p>	<p>Fabricated from AISI SAE Classification 1005 or 1008.</p> <p>Conforms to Requirements of ASTM A641 for regular zinc coated wire.</p> <p>Typical Tensile Range – 55,000 to 70,000 psi</p>												
 <p>100% American Labor and Materials.</p>	<p>Specs and Support Properties:</p> <table border="1"><thead><tr><th>Gauge</th><th>Decimal Equivalent</th><th>Weight Capacity</th></tr></thead><tbody><tr><td>12</td><td>0.105" diameter</td><td>431 lbs per pc</td></tr><tr><td>9</td><td>0.148" diameter</td><td>1,188 lbs per pc</td></tr><tr><td>8</td><td>0.160" diameter</td><td>1,695 lbs per pc</td></tr></tbody></table> <p>Weight Capacity Loads are Based on Yield Strength Testing in Accordance with ASTM A370-10</p>	Gauge	Decimal Equivalent	Weight Capacity	12	0.105" diameter	431 lbs per pc	9	0.148" diameter	1,188 lbs per pc	8	0.160" diameter	1,695 lbs per pc
Gauge	Decimal Equivalent	Weight Capacity											
12	0.105" diameter	431 lbs per pc											
9	0.148" diameter	1,188 lbs per pc											
8	0.160" diameter	1,695 lbs per pc											

9802 Widmer Rd, Lenexa, KS 66215



P: 913.888.2929 - FAX: 913.888.4405

www.QSWMFG.com